

TECHNICAL SPECIFICATIONS



Model Name	VST ZETOR 5011	VST ZETOR 4511	VST ZETOR 4211
ENGINE			
Power at Rated RPM (HP)	49 @ 2100	45@ 2100	42@ 2100
No. of Cylinder	3	3	3
Displacement(CC)	2942	2942	2942
Air Cleaner	Dry Type	Dry Type	Dry Type
Torque Nm	205	190	180
PTO			
PTO HP	43.6	40.2	37
PTO Type	540/ GSPTO	540/ GSPTO	540/ GSPTO
TRANSMISSION			
Transmission Type	Helical Constant Mesh	Helical Constant Mesh	He l ical Constant Mesh
No. of Gears	8+2	8+2	8+2
Shifting	Side Shift	Side Shift	Side Shift
Rear Axle Reduction	BullGear Pinion	BullGear Pinion	BullGear Pinion
Front Axle Reduction	Straight Ax l e	Straight Axle	Straight Axle
SPEED & CLUTCH			
Speed forward(kmph)	2.6 - 34.1	2.4 - 32.5	2.3 - 3.1
Speed reverse(kmph)	3.2 - 12.7	3.1 - 121	2.9 - 11.6
Forward Speed at flyup	37.1	35.5	33.9
Clutch	Dual	Dual	Dual/Single*
BRAKES			
Туре	O I B	OIB	O I B
STEERING			
Туре	Power Steering	Power Steering	Power Steering
SEAT			
Туре	Premium VZ Seat	Premium VZ Seat	Premium VZ Seat

Model Name	VST ZETOR 5011	VST ZETOR 4511	VST ZETOR 4211
FUEL TANK			
Capacity (Litre)	60	60	60
HYDAULICS			
Three Point Linkage	CAT II	CAT II	CATII
VZ Matic	yes	yes	yes
Lifting Capacity (kg)	ADDC - 1800 KG	ADDC - 1800 KG	ADDC - 1800 KG
Spool Value	DCV	DCV	DCV/QRC*
WHEEL			
Wheel drive	2WD	2WD	2WD
Front	7.5X16/6.5X16*	6.5X16/6X16*	6X16
Rear	16.9X28/14.9X28*	14.9X28/13.6X28*	13.6X28
ELECTRICAL			
Battery	12 V ,88AH	12 V ,88AH	12V,88AH
Alternator	12V,50A	12V,50A	12V,50A
Starter Motor	12V,2.7KV	12V,2.7KV	12V,2.7KV
DIMENISIONS			
Overall Length(mm)	3570	3570	3570
Overall Width(mm)	1930	1820	1750
Overall Height(mm)	2120	2110	2090
Ground Clearance(mm)	460	440	420
Wheel Base (mm)	2100	2100	2100
TCR with Brakes (mm)	3.1	3.1	3.1
Total Weight (kgf) W/O ACCESSIORIES	2210	2140	2080
*Optional			

VST ZETOR PRIVATE LIMITED

Plot No-1, Dyavasandra Industrial Layout, Mahadevapura, Bengaluru - 560048, Karnataka, India. e-mail: info@vstzetor.com; www.vstzetor.com CIN: U28211KA2023PTC179152



SCAN TO FOLLOW US ON SOCIAL MEDIA



Please contact your nearest dealership for latest updates

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only.

Product specifications are subject to change without prior notice.

Performance of the machine may vary with user/field/working conditions.